

## Garant

### Fluteless machine tap with oil grooves HSS-E-PM Form C 6HX, TiN, M: M3,5



#### Order data

Order number	139178 M3,5
GTIN	4045197509109
Item class	11H

#### Description

##### Version:

**DIN 2174** ( $\approx$  DIN 371  $\leq$  M10;  $\approx$  DIN 376  $\geq$  M12). **With oil grooves; optimum lubrication effect even in deeper threads.**

**Tolerance class:** ISO 2X/6HX.

The **innovative polygon form** permits a wide application spectrum. The **multi-function layer structure** achieves **maximum service life** even in **high-tensile materials**.

Tolerance class: ISO 2X 6HX

Thread pitch: 0.6 mm

Overall length L: 56 mm

Shank  $\varnothing D_s$ : 4 mm

Shank square  $\square$ : 3 mm

Tapping hole  $\varnothing$  with guide value: 3.25 mm

#### Technical description

Number of cutting edges Z	3
Thread pitch	0.6 mm
Number of clamping slots	3
Thread $\varnothing$	3.5 mm
Shank $\varnothing D_s$	4 mm
Shank square $\square$	3 mm
Overall length L	56 mm
Tapping hole $\varnothing$ with guide value	3.25 mm

Tolerance class	ISO 2X 6HX
Thread depth	10.5 mm
Thread size	M3.5
Coating	TiN
Thread type	M
Flank angle	60 degrees
Tool material	HSS E PM
Standard	DIN 2174
Thread standard	DIN 13
Taper lead form	C
Shank	Plain shank with h9
Through-coolant	no
Application for type of drilling	up to 3×D for blind holes and through holes
Cutting direction	right-hand
Colour ring	green
Type of product	Fluteless tap