

Garant
Synchronised fluteless machine tap with oil grooves HSS-E-PM Form C, TiN, M: M2,5

Order data

Order number	139210 M2,5
GTIN	4045197705822
Item class	11H

Description
Version:

Special polygon geometry and shank to DIN 1835-B for machines with synchronised spindle drive. With oil grooves; optimal lubrication effect even in deeper threads.

The **innovative polygon form** permits a wide application spectrum. The **multi-function layered coating** achieves **maximum service life** even in **high-tensile materials** in **fixed** applications.

Note:

For use on synchronised spindles, the GARANT quick-change tapping chuck No. 338100 – 338121 with minimum length adjustment (MLA) ensures the highest process reliability.

Tolerance class: ISO 2X 6HX

Thread pitch: 0.45 mm

Overall length L: 70 mm

Shank Ø D_s: 6 mm

Shank square □: 4.9 mm

Tapping hole Ø with guide value: 2.3 mm

Technical description

Number of cutting edges Z	3
Thread pitch	0.45 mm
Thread Ø	2.5 mm
Number of clamping slots	3
Shank Ø D _s	6 mm
Shank square □	4.9 mm

Overall length L	70 mm
Tapping hole Ø with guide value	2.3 mm
Tolerance class	ISO 2X 6HX
Thread depth	6.25 mm
Thread size	M2.5
Coating	TiN
Thread type	M
Flank angle	60 degrees
Tool material	HSS E PM
Standard	Manufacturer's standard
Thread standard	DIN 13
Taper lead form	C
Shank	DIN 1835 B with h6
Through-coolant	no
Application for type of drilling	up to 2.5×D for blind holes and through holes
Cutting direction	right-hand
Shank tolerance	h6
Colour ring	green
Type of product	Fluteless tap