

Garant
Fluteless machine tap with oil grooves HSS-E-PM, TiAlN, G: G1/8

Order data

Order number	139395 G1/8
GTIN	4045197705860
Item class	11H

Description
Version:

DIN 2189 (\approx DIN 5156). **With oil grooves; optimum lubrication effect even in deeper threads.**

The **innovative polygon form** permits a wide application spectrum. The **multi-function layer structure** achieves **maximum service life** even in **high-tensile materials**.

Special **TiAlN coating**, highly suitable **for aluminium alloys**.

Application:

For **Whitworth parallel pipe threads** DIN-ISO 228/1 (threads that do not form a seal within the connection).

Thread pitch: 0.907 mm

Threads per inch: 28

Thread \varnothing : 9.728 mm

Overall length L: 90 mm

Shank \varnothing D_s: 7 mm

Shank square \square : 5.5 mm

Technical description

Thread \varnothing	9.728 mm
Number of cutting edges Z	6
Thread pitch	0.907 mm
Threads per inch	28
Number of clamping slots	6
Shank \varnothing D _s	7 mm
Shank square \square	5.5 mm

Overall length L	90 mm
Tapping hole Ø with guide value	9.25 mm
Thread depth	29.19 mm
Thread size	G1/8
Coating	TiAlN
Thread type	G
Flank angle	55 degrees
Tool material	HSS E PM
Standard	DIN 2189
Tolerance class	ISO 228 X
Taper lead form	C
Shank	Plain shank with h9
Through-coolant	no
Application for type of drilling	up to 3×D for blind holes and through holes
Cutting direction	right-hand
Colour ring	yellow