

Garant
Fluteless machine tap with oil grooves HSS-E-PM, TiN, G: G1/2

Order data

Order number	139400 G1/2
GTIN	4045197509635
Item class	11H

Description
Version:

DIN 2189 (≈ DIN 5156). **With oil grooves; optimum lubrication effect even in deeper threads.** The **innovative polygon form** permits a wide application spectrum. The **multi-function layer structure** achieves **maximum service life** even in **high-tensile materials**.

Application:

For **Whitworth parallel pipe threads** DIN-ISO 228/1 (threads that do not form a seal within the connection).

Thread pitch: 1.814 mm

Threads per inch: 14

Thread Ø: 20.96 mm

Overall length L: 125 mm

Shank Ø D_s: 16 mm

Shank square □: 12 mm

Technical description

Thread Ø	20.96 mm
Number of cutting edges Z	6
Number of clamping slots	6
Thread pitch	1.814 mm
Threads per inch	14
Shank Ø D _s	16 mm
Shank square □	12 mm

Overall length L	125 mm
Tapping hole Ø with guide value	20.05 mm
Thread depth	62.88 mm
Thread size	G1/2
Coating	TiN
Thread type	G
Flank angle	55 degrees
Tool material	HSS E PM
Standard	DIN 2189
Tolerance class	ISO 228 X
Taper lead form	C
Shank	Plain shank with h9
Through-coolant	no
Application for type of drilling	up to 3×D for blind holes and through holes
Cutting direction	right-hand
Colour ring	blue