

GARANT Master TM plain shank thread mill 2×D, TiAlN, M: M14



Order data

Order number	139640 M14
GTIN	4045197957528
Item class	11D

Description

Version:

Solid carbide thread mills with irregular cutting edge spacing and an increased number of cutting edges. Due to the irregular cutting edge spacing they achieve very smooth running and long tool life.

Newly developed universal geometry and **high-performance coating** for use across a wide spectrum of materials.

- · Significantly reduced vibration due to irregular cutting edge spacing
- · Increased number of cutting edges
- · New coating for optimum wear resistance
- · Corrected thread profile for avoidance of profile distortions

Through-coolant feed ≥ M4

Note:

Form HB and HE supplied at the same price as HA.

Form **HB**: order with **No. 139640 / 136941 + 129100 HB**Form **HE**: order with **No. 139640 / 136941 + 129100 HE**.

Through-coolant: yes

No. of teeth Z: 6 Thread pitch: 2 mm Nominal Ø D_c: 11.5 mm

maximum insertion depth L₁: 29 mm

Shank length L_s: 45 mm Overall length L: 82 mm Shank Ø D_s: 12 mm

Technical description

No. of teeth Z	6

Number of clamping slots	6
maximum insertion depth L ₁	29 mm
Feed f _z in steel < 750 N/mm ²	0.1 mm
Thread pitch	2 mm
Thread depth	28 mm
Shank length L _s	45 mm
Shank Ø D _s	12 mm
Through-coolant	yes
Overall length L	82 mm
Thread size	M14
Nominal Ø D _c	11.5 mm
Coating	TiAIN
Thread type	M-LH
Thread type	M
Flank angle	60 degrees
Tool material	Solid carbide
Thread standard	DIN 13
Shank	DIN 6535 HA to h6
Application for type of drilling	up to 2×D for blind holes and through holes
Spacing of the cutters	unequal spacing
Shank tolerance	h6
Colour ring	green
Internal/external application	Indvendig
Series	GARANT Master TM
Type of product	thread milling cutter
Services	

© Hoffmann GmbH Qualitätswerkzeuge

Shank grinding Type HB

129100 HB 129100 HE



Shank grinding Type HE