


Garant
GARANT Master TM plain shank thread mill 2×D, TiAlN, M: M24

Order data

Order number	139640 M24
GTIN	4045197957559
Item class	11D

Description
Version:

Solid carbide thread mills **with irregular cutting edge spacing and an increased number of cutting edges**. Due to the **irregular cutting edge spacing** they achieve **very smooth running** and **long tool life**.

Newly developed universal geometry and **high-performance coating** for use across a wide spectrum of materials.

- **Significantly reduced vibration due to irregular cutting edge spacing**
- **Increased number of cutting edges**
- **New coating for optimum wear resistance**
- **Corrected thread profile for avoidance of profile distortions**

Through-coolant feed \geq M4

Note:

Form HB and HE supplied at the same price as HA.

Form **HB**: order with **No. 139640 / 136941 + 129100 HB**

Form **HE**: order with **No. 139640 / 136941 + 129100 HE**.

Through-coolant: yes

No. of teeth Z: 6

Thread pitch: 3 mm

Nominal $\varnothing D_c$: 19.95 mm

maximum insertion depth L_1 : 49.5 mm

Shank length L_s : 50 mm

Overall length L: 120 mm

Shank $\varnothing D_s$: 20 mm

Technical description

Shank length L_s	50 mm
--------------------	-------

Overall length L	120 mm
Thread depth	48 mm
No. of teeth Z	6
Number of clamping slots	6
Shank $\varnothing D_s$	20 mm
Through-coolant	yes
Thread pitch	3 mm
Feed f_z in steel $< 750 \text{ N/mm}^2$	0.15 mm
maximum insertion depth L_1	49.5 mm
Thread size	M24
Nominal $\varnothing D_c$	19.95 mm
Coating	TiAlN
Thread type	M-LH
Thread type	M
Flank angle	60 degrees
Tool material	Solid carbide
Thread standard	DIN 13
Shank	DIN 6535 HA to h6
Application for type of drilling	up to $2 \times D$ for blind holes and through holes
Spacing of the cutters	unequal spacing
Shank tolerance	h6
Colour ring	green
Internal/external application	Indvendig
Series	GARANT Master TM
Type of product	thread milling cutter

Services

Shank grinding Type HB	129100 HB
	129100 HE

Shank grinding Type HE
