

Garant
Plain shank thread mill 1.5×D, TiAlN, M: M8

Order data

Order number	139652 M8
GTIN	4045197199669
Item class	11J

Description
Version:

Corrected thread profile for milling **exact internal threads** (ensure stable clamping conditions).

Incorporating a **countersink profile** for a 90° countersink.

Advantage:

Countersinking and thread milling in one operation!

Through-coolant: no

No. of teeth Z: 4

Thread pitch: 1.25 mm

Nominal $\varnothing D_C$: 6.22 mm

Shank length L_S : 40 mm

Overall length L: 70 mm

Shank $\varnothing D_S$: 10 mm

Neck $\varnothing D_1$: 9 mm

Technical description

Feed f_z in steel < 60 HRC	0.015 mm
Number of clamping slots	4
Thread pitch	1.25 mm
No. of teeth Z	4
Shank $\varnothing D_S$	10 mm
Overall length L	70 mm

Shank length L_s	40 mm
Through-coolant	no
Thread depth	12 mm
Thread size	M8
Nominal $\varnothing D_c$	6.22 mm
Programming value for countersink L_1	14.1 mm
Neck $\varnothing D_1$	9 mm
Coating	TiAlN
Thread type	M-LH
Thread type	M
Flank angle	60 degrees
Tool material	Solid carbide
Thread standard	DIN 13
Shank	DIN 6535 HA with h6
Application for type of drilling	up to 1.5xD for blind holes and through holes
Countersink angle	90 degrees
Shank tolerance	h6
Colour ring	red
Internal/external application	Internal
Type of product	thread milling cutter