

GARANT Master TM plain shank thread mill 2×D, TiAlN, MF: 4X0,5



Order data

Order number	139665 4X0,5
GTIN	4045197957566
Item class	11D

Description

Version:

Solid carbide thread milling cutters with irregular cutting edge spacing and an increased number of cutting edges. Due to the irregular cutting edge spacing they achieve very smooth running and long tool life.

Newly developed universal geometry and **high-performance coating** for use across a wide spectrum of materials.

- · Significantly reduced vibration due to irregular cutting edge spacing
- · Increased number of cutting edges
- New coating for optimum wear resistance
- · Corrected thread profile for avoidance of profile distortions

Through-coolant feed \ge 4×0.5

Note:

Form HB and HE supplied at the same price as HA. Form HB: order with No. 139665 + 129100 HB Form HE: order with No. 139665 + 129100 HE

Through-coolant: no No. of teeth Z: 4 Thread pitch: 0.5 mm Nominal Ø D_c: 3.29 mm

maximum insertion depth L₁: 8.25 mm

Shank length L; 36 mm Overall length L: 58 mm Shank Ø D; 6 mm

Technical description

Thread depth	8 mm

Feed f_z in steel < 750 N/mm ²	0.02 mm
Through-coolant	no
Overall length L	58 mm
Shank length L _s	36 mm
Number of clamping slots	4
No. of teeth Z	4
Shank Ø D _s	6 mm
Thread pitch	0.5 mm
maximum insertion depth L ₁	8.25 mm
Thread size	M4×0.5
Nominal Ø D _c	3.29 mm
Coating	TiAlN
Thread type	MF
Thread type	MF-LH
Flank angle	60 degrees
Tool material	Solid carbide
Thread standard	DIN 13
Shank	DIN 6535 HA to h6
Application for type of drilling	up to 2×D for blind holes and through holes
Spacing of the cutters	unequal spacing
Colour ring	green
Internal/external application	Indvendig
Series	GARANT Master TM
Type of product	thread milling cutter

Services

Shank grinding Type HB	129100 HB
Shank grinding Type HE	129100 HE

