

Garant

GARANT Master TM plain shank thread mill 2×D, TiAlN, MF: 6X0,75



Order data

Order number	139665 6X0,75
GTIN	4045197957580
Item class	11D

Description

Version:

Solid carbide thread milling cutters **with irregular cutting edge spacing and an increased number of cutting edges**. Due to the **irregular cutting edge spacing** they achieve **very smooth running** and **long tool life**.

Newly developed universal geometry and **high-performance coating** for use across a wide spectrum of materials.

- **Significantly reduced vibration due to irregular cutting edge spacing**
- **Increased number of cutting edges**
- **New coating for optimum wear resistance**
- **Corrected thread profile for avoidance of profile distortions**

Through-coolant feed $\geq 4 \times 0.5$

Note:

Form HB and HE supplied at the same price as HA.

Form **HB**: order with **No. 139665 + 129100 HB**

Form **HE**: order with **No. 139665 + 129100 HE**

Through-coolant: yes

No. of teeth Z: 4

Thread pitch: 0.75 mm

Nominal $\varnothing D_c$: 4.9 mm

maximum insertion depth L_1 : 12.38 mm

Shank length L_s : 36 mm

Overall length L: 58 mm

Shank $\varnothing D_s$: 6 mm

Technical description

Through-coolant	yes
-----------------	-----

Thread depth	12 mm
Shank length L_s	36 mm
maximum insertion depth L_1	12.38 mm
No. of teeth Z	4
Overall length L	58 mm
Thread pitch	0.75 mm
Feed f_z in steel $< 750 \text{ N/mm}^2$	0.05 mm
Number of clamping slots	4
Shank $\varnothing D_s$	6 mm
Thread size	M6×0.75
Nominal $\varnothing D_c$	4.9 mm
Coating	TiAlN
Thread type	MF
Thread type	MF-LH
Flank angle	60 degrees
Tool material	Solid carbide
Thread standard	DIN 13
Shank	DIN 6535 HA to h6
Application for type of drilling	up to 2×D for blind holes and through holes
Spacing of the cutters	unequal spacing
Colour ring	green
Internal/external application	Indvendig
Series	GARANT Master TM
Type of product	thread milling cutter

Services

Shank grinding Type HB	129100 HB
Shank grinding Type HE	129100 HE

