

# GARANT Master TM plain shank thread mill with countersink 2×D, TiAIN, MF: 12X1,5



#### **Order data**

Order number	139682 12X1,5
GTIN	4045197957962
Item class	11D

### **Description**

#### Version:

Solid carbide thread milling cutters with irregular cutting edge spacing and an increased number of cutting edges. Due to the irregular cutting edge spacing they achieve very smooth running and long tool life.

**Newly developed universal geometry** and **high-performance coating** for use across a wide spectrum of materials.

- · Significantly reduced vibration due to irregular cutting edge spacing
- Increased number of cutting edges
- · New coating for optimum wear resistance
- Corrected thread profile for avoidance of profile distortions

#### **Advantage:**

Incorporating a countersink profile for a 90° countersink and thread milling in a single operation.

#### Note

Form HB and HE supplied at the same price as HA

Form **HB**: order with **No. 139682 + 129100 HB** 

Form **HE**: order with **No. 139682 + 129100 HE** 

Form **HB**: order with **No. 139683 + 129100 HB** 

Form **HE**: order with **No. 139683 + 129100 HE** 

Order HB shank: with No. 139682 + 129100 HB

Order HE shank: with No. 139682 + 129100 HE

Through-coolant: yes

No. of teeth Z: 6

Thread pitch: 1.5 mm Nominal  $\varnothing$  D<sub>c</sub>: 10 mm Shank length L<sub>s</sub>: 45 mm Overall length L: 94 mm

Shank Ø D<sub>s</sub>: 14 mm

maximum countersink Ø D₁: 12.5 mm

## **Technical description**

Thread pitch	1.5 mm
Overall length L	94 mm
Through-coolant	yes
maximum countersink $\emptyset$ D <sub>1</sub>	12.5 mm
Shank length L₅	45 mm
Shank Ø D <sub>s</sub>	14 mm
Feed $f_z$ in steel < 750 N/mm <sup>2</sup>	0.09 mm
No. of teeth Z	6
Thread depth	24 mm
Programming value for countersink $I_1$	26 mm
Number of clamping slots	6
Thread size	M12×1.5
Nominal Ø D <sub>c</sub>	10 mm
Coating	TiAlN
Thread type	MF
Thread type	MF-LH
Flank angle	60 degrees
Tool material	Solid carbide
Thread standard	DIN 13
Shank	DIN 6535 HA to h6
Application for type of drilling	up to 2×D for blind holes and through holes
Spacing of the cutters	unequal spacing
Countersink angle	90 degrees
Colour ring	green
Internal/external application	Internal
Series	GARANT Master TM

Type of product	thread milling cutter
Services	
Shank grinding Type HE	129100 HE
Shank grinding Type HB	129100 HB