


**Garant**
**GARANT Master TM plain shank thread mill with countersink 2×D, TiAlN, MF: 8X1**

**Order data**

Order number	139682 8X1
GTIN	4045197957924
Item class	11D

**Description**
**Version:**

Solid carbide thread milling cutters **with irregular cutting edge spacing and an increased number of cutting edges**. Due to the **irregular cutting edge spacing** they achieve **very smooth running** and **long tool life**.

**Newly developed universal geometry** and **high-performance coating** for use across a wide spectrum of materials.

- **Significantly reduced vibration due to irregular cutting edge spacing**
- **Increased number of cutting edges**
- **New coating for optimum wear resistance**
- **Corrected thread profile for avoidance of profile distortions**

**Advantage:**

Incorporating a countersink profile for a 90° countersink and thread milling in a single operation.

**Note:**

Form HB and HE supplied at the same price as HA

Form **HB**: order with **No. 139682 + 129100 HB**

Form **HE**: order with **No. 139682 + 129100 HE**

Form **HB**: order with **No. 139683 + 129100 HB**

Form **HE**: order with **No. 139683 + 129100 HE**

Order **HB** shank: with **No. 139682 + 129100 HB**

Order **HE** shank: with **No. 139682 + 129100 HE**

Through-coolant: yes

No. of teeth Z: 4

Thread pitch: 1 mm

Nominal  $\varnothing D_C$ : 6.6 mm

Shank length  $L_s$ : 40 mm

Overall length L: 75 mm

Shank  $\varnothing D_s$ : 10 mm

maximum countersink  $\varnothing D_1$ : 8.5 mm

## Technical description

maximum countersink $\varnothing D_1$	8.5 mm
Thread depth	16 mm
Through-coolant	yes
Programming value for countersink $l_1$	17.45 mm
No. of teeth Z	4
Shank length $L_s$	40 mm
Shank $\varnothing D_s$	10 mm
Overall length L	75 mm
Feed $f_z$ in steel < 750 N/mm <sup>2</sup>	0.06 mm
Thread pitch	1 mm
Number of clamping slots	4
Thread size	M8×1
Nominal $\varnothing D_c$	6.6 mm
Coating	TiAlN
Thread type	MF
Thread type	MF-LH
Flank angle	60 degrees
Tool material	Solid carbide
Thread standard	DIN 13
Shank	DIN 6535 HA to h6
Application for type of drilling	up to 2×D for blind holes and through holes
Spacing of the cutters	unequal spacing
Countersink angle	90 degrees
Colour ring	green
Internal/external application	Internal
Series	GARANT Master TM

Type of product	thread milling cutter
-----------------	-----------------------

---

**Services**

Shank grinding Type HE	129100 HE
------------------------	-----------

Shank grinding Type HB	129100 HB
------------------------	-----------