Garant

GARANT Master TM plain shank thread mill with countersink 2.5×D, TiAIN, **MF: 10X1**



Order data

Order number	139683 10X1
GTIN	4045197958037
Item class	11D

Description

Version:

Solid carbide thread milling cutters with irregular cutting edge spacing and an increased number of cutting edges. Due to the irregular cutting edge spacing they achieve very smooth running and long tool life.

Newly developed universal geometry and high-performance coating for use across a wide spectrum of materials.

- · Significantly reduced vibration due to irregular cutting edge spacing
- Increased number of cutting edges
- New coating for optimum wear resistance
- · Corrected thread profile for avoidance of profile distortions

Advantage:

Incorporating a countersink profile for a 90° countersink and thread milling in a single operation. Note:

HB and HE shanks are available at the same price as HA.

Order **HB** shank: with **No. 139683 + 129100 HB** Order HE shank: with No. 139683 + 129100 HE Through-coolant: yes No. of teeth Z: 6 Thread pitch: 1 mm Nominal Ø D_c: 8.5 mm Shank length L_s: 45 mm Overall length L: 92 mm Shank Ø D_s: 12 mm

maximum countersink Ø D₁: 10.5 mm

Technical description

Programming value for countersink I1	26.5 mm
maximum countersink Ø D_1	10.5 mm
Feed f _z in steel < 750 N/mm ²	0.075 mm
Shank length L _s	45 mm
Through-coolant	yes
Thread depth	20 mm
Number of clamping slots	6
Shank Ø D _s	12 mm
Overall length L	92 mm
Thread pitch	1 mm
No. of teeth Z	6
Thread size	M10×1
Nominal Ø D _c	8.5 mm
Coating	TiAIN
Thread type	MF
Thread type	MF-LH
Flank angle	60 degrees
Tool material	Solid carbide
Thread standard	DIN 13
Shank	DIN 6535 HA to h6
Application for type of drilling	up to 2.5×D for blind holes and through holes
Spacing of the cutters	unequal spacing
Countersink angle	90 degrees
Colour ring	green
Internal/external application	Internal
Series	GARANT Master TM
Type of product	thread milling cutter

Services

Shank grinding Type HE	129100 HE
Shank grinding Type HB	129100 HB