Garant

High-precision countersink with unequal spacing and 3 drive flats 90°, TiAIN, External Ø Dc: 25 mm



Order data

Order number	150132 25
GTIN	4045197700797
Item class	11M

Description

Version:

All countersinks have 3 cutting edges. Special geometry with extremely unequal spacing and matching cutting edge preparation. Radially relief ground. Flutes ground from solid. Newly developed **special TiAIN coating** for long service life.

High-precision countersink, produced with tight manufacturing tolerances similar to DIN 335-C. Three **drive flats on the shank** for use in a 3-jaw chuck.

Advantage:

Very smooth cutting throughout the entire countersinking operation. Chatter-free running for perfect results and **optimum tool service life.**

Application:

High-precision countersinks for production of exactly round 90° countersunk surfaces. Through-coolant: no

Number of cutting edges Z: 3

Number of cutting edges Z: 3

smallest countersink $\ensuremath{\mathcal{O}}$ for holes from: 3.8 mm

Overall length L: 67 mm

Shank Ø D₅: 10 mm

for countersunk screws DIN 7991: M12

Feed f in steel $< 500 \text{ N/mm}^2$: 0.25 mm/rev.

Technical description

Feed f in steel < 500 N/mm²

0.25 mm/rev.

Shank tolerance	h9
External Ø	25 mm
for countersunk screws DIN 7991	M12
smallest countersink Ø for holes from	3.8 mm
Shank \varnothing D _s	10 mm
Overall length L	67 mm
Number of cutting edges Z	3
Coating	TiAIN
Countersink tip angle	90 degrees
Tool material	HSS
Spacing of the countersink cutting edges	unequal spacing
Standard	DIN 335 C
Shank	Shank with h9 and three drive flats
Through-coolant	no
Colour ring	green
Type of product	Stepped drill and countersink

Accessories

High-precision countersink set with 3 drive flats No. 150132	150307 5
in a case 90° Number of countersinks 5	150507 5