

Garant
High-precision countersink, long 90°, uncoated, External Ø Dc: 12,4 mm


Order data

Order number	150371 12,4
GTIN	4045197086129
Item class	11M

Description

Version:

All countersinks have 3 cutting edges, radially relief ground. Flutes ground from solid. High-precision countersink, produced to tight manufacturing tolerances similar to DIN 335-C **with long plain shank**.

Through-coolant: no

Number of cutting edges Z: 3

Number of cutting edges Z: 3

smallest countersink Ø for holes from: 2.8 mm

Overall length L: 108 mm

Shank Ø D_s: 8 mm

for countersunk screws DIN 7991: M6

Feed f in steel < 500 N/mm²: 0.12 mm/rev.

Technical description

Pre-drill Ø	2.8 mm
smallest countersink Ø for holes from	2.8 mm
Feed f in steel < 500 N/mm ²	0.12 mm/rev.
for countersunk screws DIN 7991	M6
External Ø	12.4 mm
Shank tolerance	h9
Shank Ø D _s	8 mm
Overall length L	108 mm

Number of cutting edges Z	3
Coating	uncoated
Countersink tip angle	90 degrees
Tool material	HSS
Standard	Manufacturer's standard
Shank	Plain shank with h9
Through-coolant	no
Colour ring	without
Type of product	Stepped drill and countersink