

**Garant**
**High-precision countersink, extra long 90°, uncoated, External Ø Dc: 10,4 mm**

**Order data**

Order number	150372 10,4
GTIN	4045197086174
Item class	11M

**Description**
**Version:**

**All countersinks have 3 cutting edges**, radially relief ground. Flutes ground from solid. High-precision countersink, produced to tight manufacturing tolerances similar to DIN 335-C **with extra long plain shank.**

Through-coolant: no

Number of cutting edges Z: 3

Number of cutting edges Z: 3

smallest countersink Ø for holes from: 2.5 mm

Overall length L: 157 mm

Shank Ø D<sub>s</sub>: 6 mm

for countersunk screws DIN 7991: M5

Feed f in steel < 500 N/mm<sup>2</sup>: 0.12 mm/rev.

**Technical description**

Pre-drill Ø	2.5 mm
for countersunk screws DIN 7991	M5
Feed f in steel < 500 N/mm <sup>2</sup>	0.12 mm/rev.
smallest countersink Ø for holes from	2.5 mm
External Ø	10.4 mm
Shank tolerance	h9
Shank Ø D <sub>s</sub>	6 mm
Overall length L	157 mm

Number of cutting edges Z	3
Coating	uncoated
Countersink tip angle	90 degrees
Tool material	HSS
Standard	Manufacturer's standard
Shank	Plain shank with h9
Through-coolant	no
Colour ring	without
Type of product	Stepped drill and countersink

---

## Accessories

Countersink set, extra long, No. 150372 in a case 90° Number of countersinks 6	150374 6
---	----------