

Garant
High-precision countersink, extra long 90°, uncoated, External Ø Dc: 16,5 mm

Order data

| | |
|--------------|---------------|
| Order number | 150372 16,5 |
| GTIN | 4045197086198 |
| Item class | 11M |

Description
Version:

All countersinks have 3 cutting edges, radially relief ground. Flutes ground from solid. High-precision countersink, produced to tight manufacturing tolerances similar to DIN 335-C **with extra long plain shank.**

Through-coolant: no

Number of cutting edges Z: 3

Number of cutting edges Z: 3

smallest countersink Ø for holes from: 3.2 mm

Overall length L: 161 mm

Shank Ø D_s: 10 mm

for countersunk screws DIN 7991: M8

Feed f in steel < 500 N/mm²: 0.14 mm/rev.

Technical description

| | |
|---|--------------|
| External Ø | 16.5 mm |
| for countersunk screws DIN 7991 | M8 |
| Shank tolerance | h9 |
| Feed f in steel < 500 N/mm ² | 0.14 mm/rev. |
| Pre-drill Ø | 3.2 mm |
| smallest countersink Ø for holes from | 3.2 mm |
| Shank Ø D _s | 10 mm |
| Overall length L | 161 mm |

| | |
|---------------------------|-------------------------------|
| Number of cutting edges Z | 3 |
| Coating | uncoated |
| Countersink tip angle | 90 degrees |
| Tool material | HSS |
| Standard | Manufacturer's standard |
| Shank | Plain shank with h9 |
| Through-coolant | no |
| Colour ring | without |
| Type of product | Stepped drill and countersink |