

Garant
High-precision countersink, long 90°, TiAlN, External Ø Dc: 6,3 mm

Order data

Order number	150377 6,3
GTIN	4045197867575
Item class	11M

Description
Version:

All countersinks have 3 cutting edges, radially relief ground. Flutes ground from solid. High-precision countersink, produced to tight manufacturing tolerances similar to DIN335-C, **with long plain shank.**

Special geometry with extremely unequal spacing and matching cutting edge preparation. Newly developed, **special TiAlN coating** for long tool life.

Application:

High-precision countersinks for chatter-free production of **precise, round 90° countersunk surfaces.**

Through-coolant: no

Number of cutting edges Z: 3

Number of cutting edges Z: 3

smallest countersink Ø for holes from: 1.5 mm

Overall length L: 104 mm

Shank Ø D_s: 5 mm

for countersunk screws DIN 7991: M3

Feed f in steel < 500 N/mm²: 0.1 mm/rev.

Technical description

External Ø	6.3 mm
Number of cutting edges Z	3
for countersunk screws DIN 7991	M3
Shank Ø D _s	5 mm

Shank tolerance	h9
Feed f in steel < 500 N/mm ²	0.1 mm/rev.
smallest countersink Ø for holes from	1.5 mm
Overall length L	104 mm
Pre-drill Ø	1.5 mm
Coating	TiAlN
Countersink tip angle	90 degrees
Tool material	HSS
Spacing of the countersink cutting edges	unequal spacing
Standard	Manufacturer's standard
Shank	Parallel shank to h9
Through-coolant	no
Colour ring	green
Type of product	Stepped drill and countersink