



Countersink 90°, uncoated, External Ø Dc: 30 mm



Order data

Order number	150395 30
GTIN	4045197086921
Item class	12M

Description

Version:

Countersinks radially relief ground. Chip flutes are ground from solid up to size 31. Chip angle varies with the countersink Ø for optimum chip formation. Countersink point and circumference are relief ground and cut easily.

Economy countersink version.

Note:

For countersink bits with shank 6.3 mm (1/4 inch) see Group 67.

For suitable reducing adapters for tools with MT shanks see **No. 343000-343530**.

Through-coolant: no

Number of cutting edges Z: 3

Number of cutting edges Z: 3

smallest countersink Ø for holes from: 4.2 mm

Overall length L: 112 mm

Morse taper MT: 2

for countersunk screws ISO 2009, 2010, 7046, 7047: M16

Feed f in steel < 500 N/mm²: 0.2 mm/rev.

Technical description

smallest countersink Ø for holes from	4.2 mm
for countersunk screws ISO 2009, 2010, 7046, 7047	M16
Feed f in steel < 500 N/mm ²	0.2 mm/rev.
Pre-drill Ø	4.2 mm
External Ø	30 mm

Overall length L	112 mm
Morse taper MT	2
Number of cutting edges Z	3
Coating	uncoated
Countersink tip angle	90 degrees
Tool material	HSS
Standard	DIN 335 D
Shank	MT 1-4
Through-coolant	no
Colour ring	without
Type of product	Stepped drill and countersink