



## Countersink 90°, uncoated, External Ø Dc: 40 mm



### Order data

Order number	150395 40
GTIN	4045197086969
Item class	12M

### Description

#### Version:

Countersinks radially relief ground. Chip flutes are ground from solid up to size 31. Chip angle varies with the countersink Ø for optimum chip formation. Countersink point and circumference are relief ground and cut easily.

Economy countersink version.

#### Note:

For countersink bits with shank 6.3 mm (1/4 inch) see Group 67.

For suitable reducing adapters for tools with MT shanks see **No. 343000-343530**.

Through-coolant: no

Number of cutting edges Z: 3

Number of cutting edges Z: 3

smallest countersink Ø for holes from: 10 mm

Overall length L: 140 mm

Morse taper MT: 3

Feed f in steel < 500 N/mm<sup>2</sup>: 0.25 mm/rev.

### Technical description

External Ø	40 mm
Feed f in steel < 500 N/mm <sup>2</sup>	0.25 mm/rev.
Pre-drill Ø	10 mm
smallest countersink Ø for holes from	10 mm
Overall length L	140 mm

Morse taper MT	3
Number of cutting edges Z	3
Coating	uncoated
Countersink tip angle	90 degrees
Tool material	HSS
Standard	DIN 335 D
Shank	MT 1-4
Through-coolant	no
Colour ring	without
Type of product	Stepped drill and countersink