

Garant
High-precision countersink 90°, TiN, External Ø Dc: 40 mm

Order data

Order number	150396 40
GTIN	4045197087041
Item class	11M

Description
Version:

Countersinks radially relief ground. Chip flutes are ground from solid up to size 31. Chip angle varies with the countersink Ø for optimum chip formation. Countersink point and circumference are relief ground and cut easily.

Precision countersink for considerable performance improvement.

Note:

For suitable reducing adapters for tools with MT shanks see **No. 343000-343530**.

For countersink bits with shank 6.3 mm (1/4 inch) see Group 67.

Through-coolant: no

Number of cutting edges Z: 3

Number of cutting edges Z: 3

smallest countersink Ø for holes from: 10 mm

Overall length L: 140 mm

Morse taper MT: 3

Feed f in steel < 500 N/mm²: 0.25 mm/rev.

Technical description

smallest countersink Ø for holes from	10 mm
External Ø	40 mm
Pre-drill Ø	10 mm
Feed f in steel < 500 N/mm ²	0.25 mm/rev.
Overall length L	140 mm

Morse taper MT	3
Number of cutting edges Z	3
Coating	TiN
Countersink tip angle	90 degrees
Tool material	HSS
Standard	DIN 335 D
Shank	MT 1-4
Through-coolant	no
Colour ring	without
Type of product	Stepped drill and countersink