

Garant

Precision countersinks with unequal spacing 60°, TiAlN, External Ø Dc: 10 mm



Order data

Order number	150815 10
GTIN	4045197868077
Item class	11M

Description

Version:

High-precision 60° countersink with unequal spacing.

Special geometry with extremely unequal spacing and matching cutting edge preparation. Radially relief ground. Flutes ground from solid. Newly developed **special TiAlN coating** for long service life.

Advantage:

Very smooth cutting throughout the entire countersinking operation. Chatter-free running for perfect results and **optimum tool service life**.

Application:

High-precision countersinks for production of **exactly round 60° countersunk surfaces**.

Through-coolant: no

Number of cutting edges Z: 3

Number of cutting edges Z: 3

smallest countersink Ø for holes from: 2.5 mm

Overall length L: 50 mm

Shank Ø D_s: 6 mm

Feed f in steel < 500 N/mm²: 0.13 mm/rev.

Technical description

External Ø	10 mm
Feed f in steel < 500 N/mm ²	0.13 mm/rev.
Overall length L	50 mm
smallest countersink Ø for holes from	2.5 mm

Shank $\varnothing D_s$	6 mm
Number of cutting edges Z	3
Coating	TiAlN
Countersink tip angle	60 degrees
Tool material	HSS
Spacing of the countersink cutting edges	unequal spacing
Standard	DIN 334
Shank	Parallel shank to h9
Through-coolant	no
Colour ring	green
Type of product	Stepped drill and countersink