


Garant
Countersink Form C 60°, TiAlN, External Ø Dc: 16 mm

Order data

Order number	150845 16
GTIN	4045197364777
Item class	11M

Description
Version:

The chip flutes are ground from solid. Countersink point and circumference are relief ground and cut easily. This results in easy and **chatter-free cutting** for deep countersinking, as well as for deburring or countersinking.

Application:

For chatter-free countersinking and deburring.

Especially suitable for chamfering tapped holes and for countersinking in jig and tool making.

Through-coolant: no

Number of cutting edges Z: 3

Number of cutting edges Z: 3

smallest countersink Ø for holes from: 4 mm

Overall length L: 63 mm

Shank Ø D_s: 10 mm

Feed f in steel < 500 N/mm²: 0.14 mm/rev.

Technical description

Feed f in steel < 500 N/mm ²	0.14 mm/rev.
External Ø	16 mm
smallest countersink Ø for holes from	4 mm
Shank Ø D _s	10 mm
Overall length L	63 mm

Number of cutting edges Z	3
Coating	TiAlN
Countersink tip angle	60 degrees
Tool material	HSS
Standard	DIN 334
Shank	Plain shank with h9
Through-coolant	no
Colour ring	green
Type of product	Stepped drill and countersink