

**Garant**
**Mini counterbore for through holes 180°, uncoated, Counterbore Ø D1 x pin Ø D2: 4,3X2,2 mm**

**Order data**

Order number	155700 4,3X2,2
GTIN	4045197462879
Item class	11M

**Description**
**Version:**

Spiral fluted counterbore with fixed pilot.  
DIN 373 / ISO 4206.

**Application:**

**For through hole** quality **fine** (ISO values) to DIN 69.

For socket-head screws to DIN 912, 6912, 7984, and cheese-head screws to ISO 1207 (DIN 84).

**Note:**

Size 4.6 × 2.4 is not defined in DIN.

Countersink angle: 180 degrees

Number of cutting edges Z: 3

for screw size: M2

Overall length L: 56 mm

Shank Ø D<sub>s</sub>: 4.3 mm

Feed f in steel < 500 N/mm<sup>2</sup>: 0.07 mm/rev.

**Technical description**

Number of cutting edges Z	3
Pre-drill Ø	2.2 mm
for screw size	M2
Counterbore Ø	4.3 mm
Pin Ø	2.2 mm
Feed f in steel < 500 N/mm <sup>2</sup>	0.07 mm/rev.

Shank $\varnothing D_s$	4.3 mm
Overall length L	56 mm
Step height $L_1$ 1st step with chamfer	2.5 mm
Point angle	180 degrees
Cutter length $l_c$	10 mm
Coating	uncoated
Tool material	HSS E
Standard	DIN 373
Shank	Plain shank
Countersink angle	180 degrees
Through-coolant	no
Type of product	Counterbore