

## Garant

### DIN counterbore for through holes, uncoated, Counterbore $\varnothing$ D1 x pin $\varnothing$ D2: 6,5X3,9 mm



#### Order data

Order number	156020 6,5X3,9
GTIN	4045197087683
Item class	11M

#### Description

##### Version:

Spiral fluted counterbore. The pilot  $\varnothing$  matches the intended purpose:

**f** – for through holes **fine** quality to DIN ISO 273.

**m** for through holes **medium** quality to DIN ISO 273.

##### Application:

For counterboring socket head screws DIN 912, 6912, 7984, and cheese head screws ISO 1207 (DIN 84).

Shank: Parallel shank to h9

Number of cutting edges Z: 3

for screw size: M3.5

for quality of the hole: m

Overall length L: 71 mm

Shank  $\varnothing$  D<sub>s</sub>: 5 mm

Feed f in steel < 500 N/mm<sup>2</sup>: 0.09 mm/rev.

#### Technical description

for screw size	M3.5
for quality of the hole	m
Pre-drill $\varnothing$	3.9 mm
Feed f in steel < 500 N/mm <sup>2</sup>	0.09 mm/rev.
Counterbore $\varnothing$	6.5 mm
Number of cutting edges Z	3

Pin Ø	3,9 mm
Shank Ø D <sub>s</sub>	5 mm
Overall length L	71 mm
Step height L <sub>1</sub> 1st step with chamfer	14 mm
Point angle	180 degrees
Coating	uncoated
Tool material	HSS
Standard	DIN 373
Shank	Parallel shank to h9
Through-coolant	no
Type of product	Counterbore