

Garant

DIN counterbore for through holes, uncoated, Counterbore \varnothing D1 x pin \varnothing D2: 24X15,5 mm



Order data

Order number	156120 24X15,5
GTIN	4045197087867
Item class	11M

Description

Version:

Spiral fluted counterbore. The pilot \varnothing matches the intended purpose:

f – for through holes **fine** quality to DIN ISO 273.

m for through holes **medium** quality to DIN ISO 273.

Application:

For counterboring socket head screws DIN 912, 6912, 7984, and cheese head screws ISO 1207 (DIN 84).

Note:

For suitable reducing adapters for tools with MT shanks see **No. 343000-343530**.

Shank: MT 2-3

Number of cutting edges Z: 3

for screw size: M14

for quality of the hole: m

Overall length L: 162 mm

Morse taper MT: 2

Feed f in steel < 500 N/mm²: 0.16 mm/rev.

Technical description

Feed f in steel < 500 N/mm ²	0.16 mm/rev.
for screw size	M14
Pin \varnothing	15,5 mm
Counterbore \varnothing	24 mm
Number of cutting edges Z	3

Pre-drill Ø	15.5 mm
for quality of the hole	m
Overall length L	162 mm
Morse taper MT	2
Step height L ₁ 1st step with chamfer	30 mm
Point angle	180 degrees
Coating	uncoated
Tool material	HSS
Standard	Manufacturer's standard
Shank	MT 2-3
Through-coolant	no
Type of product	Counterbore