

Garant
DIN counterbore for tapping drill holes, uncoated, Counterbore \varnothing D1 x pin \varnothing D2: 6,5X2,9 mm

Order data

Order number	156220 6,5X2,9
GTIN	4045197087904
Item class	11M

Description
Version:

Three edged, spiral fluted counterbore with fixed pilot for tapping drill holes.

Application:

For counterboring socket head screws DIN 912, 6912, 7984 and slotted cheese head screws ISO 1207 (DIN 84).

The pilot diameter matches the tapping hole diameter.

Shank: Parallel shank to h9

Number of cutting edges Z: 3

for screw size: M3.5

Overall length L: 71 mm

Shank \varnothing D_s: 5 mm

Feed f in steel < 500 N/mm²: 0.09 mm/rev.

Technical description

Number of cutting edges Z	3
Counterbore \varnothing	6.5 mm
for screw size	M3.5
Pin \varnothing	2,9 mm
Feed f in steel < 500 N/mm ²	0.09 mm/rev.
Pre-drill \varnothing	2.9 mm
Shank \varnothing D _s	5 mm

Overall length L	71 mm
Step height L ₁ 1st step with chamfer	14 mm
Point angle	180 degrees
Coating	uncoated
Tool material	HSS
Standard	DIN 373
Shank	Parallel shank to h9
Through-coolant	no
Type of product	Counterbore