

Garant
Hand reamer (like 160150) configurable, Nominal \varnothing DC: 7 mm

Order data

| | |
|--------------|---------------|
| Order number | 160200 7 |
| GTIN | 4045197926548 |
| Item class | 10N |

Description
IMPORTANT: item is configurable

 Nominal \varnothing D_c: 7 mm

 \varnothing range: 6.701 - 7.1 mm, Intervall: 0,001

Version:

With **left-hand helix** 7 – 8° and long taper lead, more than 1/4 of the cutting length. An even number of teeth with irregular spacing for accurately round holes, free of chatter. The cylindrical ground chamfer on the plain cutting section smooths the hole and guides the reamer.

Hand reamers **finish ground to match your specifications.**

Application:

For through holes (not for blind holes). Also very suitable for interrupted holes.

Application for type of drilling: for through holes

Number of cutting edges Z: 6

\varnothing range: 6.701 - 7.1 mm

Flute length L_c: 54 mm

Overhang L_i: 69 mm

Overall length L: 107 mm

Number of cutting edges Z: 6

Shank square □: 5.5 mm

Technical description

| | |
|--------------------------------------|----------------|
| Nominal \varnothing D _c | 7 mm |
| Shank square □ | 5.5 mm |
| Flute length L _c | 54 mm |
| \varnothing range | 6.701 - 7.1 mm |
| Overall length L | 107 mm |

| | |
|----------------------------------|------------------------------------------|
| Overhang L ₁ | 69 mm |
| Number of cutting edges Z | 6 |
| Tool material | HSS |
| Standard | DIN 206 B |
| Helix angle | 7-8 degrees |
| Application for type of drilling | for through holes |
| Colour ring | without |
| Type of product | Reaming tool with non-detachable cutters |