Garant

NC reamer H7, uncoated, Nominal Ø DC: 2,8 mm

Order data

Order number	162900 2,8
GTIN	4045197089793
Item class	110

Description

Version:

Version suitable for NC similar to DIN 212 with straight shank Ø for standard chucking especially in hydraulic chucks or high precision collet chucks. For highest concentricity and process reliability. No need to order special collets.

With long flutes and left-hand helix.

 $\leq \emptyset$ size 1.7 with 3 teeth; $\geq \emptyset$ size 1.8 even number of teeth and irregular spacing. $\leq \emptyset$ size 3.7 both ends with centre points; $\geq \emptyset$ size 3.8 both ends with centre holes.

Reamer manufacturing tolerance to DIN 1420 for H7 hole tolerance.

Note:

For reamers in 1/100 sizes see No. 162902. For reamers with diameters and fits to specification see No. 162951 Application for type of drilling: for through holes Bore \emptyset tolerance: H7 Number of cutting edges Z: 6 Bore \emptyset tolerance: H7 Flute length L_c: 15 mm Overhang L₁: 33 mm Overall length L: 61 mm Number of cutting edges Z: 6 Shank \emptyset D_c: 3 mm

Technical description

Nominal Ø D _c	2.8 mm
Feed f in steel < 750 N/mm ²	0.2 mm/rev.
Shank tolerance	h6

Overhang L ₁	33 mm
Shank Ø D _s	3 mm
Overall length L	61 mm
Flute length L_c	15 mm
Number of cutting edges Z	б
recommended drill Ø in steel < 750 N/mm ²	2.7 mm
Bore Ø tolerance	H7
Coating	uncoated
Tool material	HSS E
Standard	Manufacturer's standard
Through-coolant	no
Shank	DIN 1835 A to h6
Application for type of drilling	for through holes
Colour ring	green
Type of product	Reaming tool with non- detachable cutters