

Garant
NC reamer H7, uncoated, Nominal \varnothing DC: 5,2 mm

Order data

Order number	162900 5,2
GTIN	4045197090218
Item class	110

Description
Version:

Version suitable for NC similar to DIN 212 **with straight shank \varnothing** for **standard chucking** especially in **hydraulic chucks** or **high precision collet chucks**. For **highest concentricity** and **process reliability**. **No need to order special collets**.

With long flutes and left-hand helix.

$\leq \varnothing$ size 1.7 with 3 teeth; $\geq \varnothing$ size 1.8 even number of teeth and irregular spacing. $\leq \varnothing$ size 3.7 both ends with centre points; $\geq \varnothing$ size 3.8 both ends with centre holes.

Reamer manufacturing tolerance to DIN 1420 for H7 hole tolerance.

Note:

For reamers in **1/100 sizes** see **No. 162902**.

For reamers with **diameters and fits to specification** see **No. 162951**

Application for type of drilling: for through holes

Bore \varnothing tolerance: H7

Number of cutting edges Z: 6

Bore \varnothing tolerance: H7

Flute length L_c : 23 mm

Overhang L_1 : 57 mm

Overall length L: 86 mm

Number of cutting edges Z: 6

Shank $\varnothing D_s$: 5 mm

Technical description

Overhang L_1	57 mm
Shank tolerance	h6
Nominal $\varnothing D_c$	5.2 mm

Feed f in steel < 750 N/mm ²	0.2 mm/rev.
Shank Ø D _s	5 mm
Overall length L	86 mm
Flute length L _c	23 mm
Number of cutting edges Z	6
recommended drill Ø in steel < 750 N/mm ²	5 mm
Bore Ø tolerance	H7
Coating	uncoated
Tool material	HSS E
Standard	Manufacturer's standard
Through-coolant	no
Shank	DIN 1835 A to h6
Application for type of drilling	for through holes
Colour ring	green
Type of product	Reaming tool with non-detachable cutters