

Garant
NC reamer H7, uncoated, Nominal Ø DC: 9,2 mm

Order data

| | |
|--------------|---------------|
| Order number | 162900 9,2 |
| GTIN | 4045197090768 |
| Item class | 110 |

Description
Version:

Version suitable for NC similar to DIN 212 **with straight shank Ø** for **standard chucking** especially in **hydraulic chucks** or **high precision collet chucks**. For **highest concentricity** and **process reliability**. **No need to order special collets**.

With long flutes and left-hand helix.

≤ Ø size 1.7 with 3 teeth; ≥ Ø size 1.8 even number of teeth and irregular spacing. ≤ Ø size 3.7 both ends with centre points; ≥ Ø size 3.8 both ends with centre holes.

Reamer manufacturing tolerance to DIN 1420 for H7 hole tolerance.

Note:

For reamers in **1/100 sizes** see **No. 162902**.

For reamers with **diameters and fits to specification** see **No. 162951**

Application for type of drilling: for through holes

Bore Ø tolerance: H7

Number of cutting edges Z: 6

Bore Ø tolerance: H7

Flute length L_c : 36 mm

Overhang L_1 : 83 mm

Overall length L: 125 mm

Number of cutting edges Z: 6

Shank Ø D_s : 10 mm

Technical description

| | |
|---|--------------|
| Shank tolerance | h6 |
| Feed f in steel < 750 N/mm ² | 0.25 mm/rev. |
| Overhang L_1 | 83 mm |

| | |
|--|--|
| Nominal $\varnothing D_c$ | 9.2 mm |
| Shank $\varnothing D_s$ | 10 mm |
| Overall length L | 125 mm |
| Flute length L_c | 36 mm |
| Number of cutting edges Z | 6 |
| recommended drill \varnothing in steel < 750 N/mm ² | 9 mm |
| Bore \varnothing tolerance | H7 |
| Coating | uncoated |
| Tool material | HSS E |
| Standard | Manufacturer's standard |
| Through-coolant | no |
| Shank | DIN 1835 A to h6 |
| Application for type of drilling | for through holes |
| Colour ring | green |
| Type of product | Reaming tool with non-detachable cutters |