

Garant
NC reamer, uncoated, Nominal \varnothing DC: 12,5 mm

Order data

| | |
|--------------|---------------|
| Order number | 162951 12,5 |
| GTIN | 4045197366238 |
| Item class | 110 |

Description
IMPORTANT: item is configurable

 Nominal \varnothing D_c: 12.5 mm

 \varnothing range: 12.06 - 12.6 mm, Intervall: 0,001

Version:
Reamers finish ground to fit your specifications.
Note:

 For **fit H7** see No. 162900 and 163000.

For reamers in 1/100 - sizes see No. 162902.

Application for type of drilling: for through holes

Number of cutting edges Z: 6

 \varnothing range: 12.06 - 12.6 mm

 Flute length L_c: 44 mm

 Overhang L₁: 110 mm

Overall length L: 151 mm

Number of cutting edges Z: 6

 Shank \varnothing D_s: 10 mm

Technical description

| | |
|---|--------------|
| Overhang L ₁ | 110 mm |
| Nominal \varnothing D _c | 12.5 mm |
| Shank tolerance | h6 |
| Feed f in steel < 750 N/mm ² | 0.25 mm/rev. |
| Shank \varnothing D _s | 10 mm |
| Overall length L | 151 mm |

| | |
|----------------------------------|--|
| Flute length L _c | 44 mm |
| Ø range | 12.06 - 12.6 mm |
| Number of cutting edges Z | 6 |
| Coating | uncoated |
| Tool material | HSS E |
| Standard | Manufacturer's standard |
| Through-coolant | no |
| Shank | DIN 1835 A to h6 |
| Application for type of drilling | for through holes |
| Colour ring | without |
| Type of product | Reaming tool with non-detachable cutters |