

Garant
Machine reamer H7, uncoated, Nominal \varnothing DC: 5 mm

Order data

Order number	163000 5
GTIN	4045197252869
Item class	110

Description
Version:

With long flutes and left-hand helix.
 From size 1.8 even number of teeth and uneven spacing.
 Up to size 3.7 both ends with external centres;
 from size 3.9 both ends with internal centres.

Reamers finish ground for fit H7.
Application:

For reaming through holes. Also suitable for blind holes (from 3.9 mm \varnothing) due to short chamfer lead.

Note:

- **Straight flute machine chucking reamers – available ex-stock.**
- **For reamers with other diameters and fits see No. 162951.**

Application for type of drilling: for through holes

Bore \varnothing tolerance: H7

Number of cutting edges Z: 6

Bore \varnothing tolerance: H7

Flute length L_c : 23 mm

Overhang L_1 : 57 mm

Overall length L: 86 mm

Number of cutting edges Z: 6

Shank \varnothing D_s : 5 mm

Technical description

Nominal \varnothing D_c	5 mm
Feed f in steel < 750 N/mm ²	0.2 mm/rev.

Shank tolerance	h9
Overhang L_1	57 mm
Shank $\varnothing D_s$	5 mm
Overall length L	86 mm
Flute length L_c	23 mm
Number of cutting edges Z	6
recommended drill \varnothing in steel $< 750 \text{ N/mm}^2$	4.9 mm
Bore \varnothing tolerance	H7
Coating	uncoated
Tool material	HSS E
Standard	DIN 212 B
Through-coolant	no
Shank	Plain shank with h9
Application for type of drilling	for through holes
Colour ring	without
Type of product	Reaming tool with non-detachable cutters