Garant

Machine reamer H7, uncoated, Nominal Ø DC: 6,5 mm



Order data

Order number	163000 6,5
GTIN	4045197252982
Item class	110

Description

Version:

With long flutes and left-hand helix.

From size 1.8 even number of teeth and uneven spacing.

Up to size 3.7 both ends with external centres;

from size 3.9 both ends with internal centres.

Reamers finish ground for fit H7.

Application:

For reaming through holes. Also suitable for blind holes (from 3.9 mm \emptyset) due to short chamfer lead.

Note:

· Straight flute machine chucking reamers – available ex-stock.

$\cdot\,$ For reamers with other diameters and fits see No. 162951.

Application for type of drilling: for through holes Bore Ø tolerance: H7 Number of cutting edges Z: 6 Bore Ø tolerance: H7 Flute length L_c: 28 mm Overhang L₁: 64 mm Overall length L: 101 mm Number of cutting edges Z: 6 Shank Ø D_s: 6.3 mm

Technical description

Shank tolerance	h9
Overhang L ₁	64 mm

Feed f in steel < 750 N/mm ²	0.2 mm/rev.
Nominal Ø D _c	6.5 mm
Shank Ø D _s	6.3 mm
Overall length L	101 mm
Flute length L _c	28 mm
Number of cutting edges Z	6
recommended drill \emptyset in steel < 750 N/mm ²	6.3 mm
Bore Ø tolerance	H7
Coating	uncoated
Tool material	HSS E
Standard	DIN 212 B
Through-coolant	no
Shank	Plain shank with h9
Application for type of drilling	for through holes
Colour ring	without
Type of product	Reaming tool with non- detachable cutters