

Garant

Solid carbide NC machine reamer, uncoated, Nominal \varnothing DC: 6,6 mm



Order data

Order number	164340 6,6
GTIN	4045197093714
Item class	11P

Description

Version:

Version suitable for NC similar to DIN 8093 **with straight shank \varnothing** for **standard chucking** especially in **hydraulic chucks** or **high precision collet chucks**. This gives **very high concentricity** and **process reliability** when manufacturing H7 fits. **No need to procure special collets when using GARANT NC reamers**. With long flutes and left-hand helix.

Application:

For reaming through holes, as the chips are evacuated in the cutting direction. Lead taper is suitable also for blind holes.

Note:

For reamers like No. 164340 and 164341 but with other diameters and fits see No. 164344 and 164345.

Application for type of drilling: for through holes

Bore \varnothing tolerance: H7

Number of cutting edges Z: 6

Bore \varnothing tolerance: H7

Flute length L_c : 26 mm

Overhang L_1 : 59 mm

Overall length L: 101 mm

Number of cutting edges Z: 6

Shank \varnothing D_s : 8 mm

Technical description

Shank tolerance	h6
Nominal \varnothing D_c	6.6 mm
Overhang L_1	59 mm

Feed f in steel < 1100 N/mm ²	0.14 mm/rev.
Shank Ø D _s	8 mm
Overall length L	101 mm
Flute length L _c	26 mm
Number of cutting edges Z	6
recommended drill Ø in steel < 1100 N/mm ²	6.4 mm
Bore Ø tolerance	H7
Coating	uncoated
Tool material	Solid carbide
Standard	Manufacturer's standard
Through-coolant	no
Shank	DIN 6535 HA with h6
Application for type of drilling	for through holes
Colour ring	green
Type of product	Reaming tool with non-detachable cutters