

**Garant**
**Solid carbide NC machine reamer, uncoated, Nominal  $\varnothing$  DC: 8,02 mm**

**Order data**

Order number	164340 8,02
GTIN	4045197093868
Item class	11P

**Description**
**Version:**

**Version suitable for NC** similar to DIN 8093 **with straight shank  $\varnothing$**  for **standard chucking** especially in **hydraulic chucks** or **high precision collet chucks**. This gives **very high concentricity** and **process reliability** when manufacturing H7 fits. **No need to procure special collets when using GARANT NC reamers**. With long flutes and left-hand helix.

**Application:**

For reaming through holes, as the chips are evacuated in the cutting direction. Lead taper is suitable also for blind holes.

**Note:**

For reamers like No. 164340 and 164341 but with other diameters and fits see No. 164344 and 164345.

Application for type of drilling: for through holes

Bore  $\varnothing$  tolerance: H7

Number of cutting edges Z: 6

Bore  $\varnothing$  tolerance: H7

Flute length  $L_c$ : 33 mm

Overhang  $L_1$ : 75 mm

Overall length L: 117 mm

Number of cutting edges Z: 6

Shank  $\varnothing$   $D_s$ : 8 mm

**Technical description**

Nominal $\varnothing$ $D_c$	8.02 mm
Overhang $L_1$	75 mm
Shank tolerance	h6

Feed f in steel < 1100 N/mm <sup>2</sup>	0.15 mm/rev.
Shank Ø D <sub>s</sub>	8 mm
Overall length L	117 mm
Flute length L <sub>c</sub>	33 mm
Number of cutting edges Z	6
recommended drill Ø in steel < 1100 N/mm <sup>2</sup>	7.7 mm
Bore Ø tolerance	H7
Coating	uncoated
Tool material	Solid carbide
Standard	Manufacturer's standard
Through-coolant	no
Shank	DIN 6535 HA with h6
Application for type of drilling	for through holes
Colour ring	green
Type of product	Reaming tool with non-detachable cutters