

Garant

Solid carbide NC machine reamer, TiAlN, Nominal Ø DC: 4,03 mm



Order data

| | |
|--------------|---------------|
| Order number | 164341 4,03 |
| GTIN | 4045197464378 |
| Item class | 11P |

Description

Version:

Version suitable for NC similar to DIN 8093 **with straight shank Ø** for **standard chucking** especially in **hydraulic chucks** or **high precision collet chucks**. This gives **very high concentricity** and **process reliability** when manufacturing H7 fits. **No need to procure special collets when using GARANT NC reamers**. With long flutes and left-hand helix.

Application:

For reaming through holes, as the chips are evacuated in the cutting direction. Lead taper is suitable also for blind holes.

Note:

For reamers like No. 164340 and 164341 but with other diameters and fits see No. 164344 and 164345.

Application for type of drilling: for through holes

Bore Ø tolerance: H7

Number of cutting edges Z: 4

Bore Ø tolerance: H7

Flute length L_c : 21 mm

Overhang L_1 : 43 mm

Overall length L: 77 mm

Number of cutting edges Z: 4

Shank Ø D_s : 4 mm

Technical description

| | |
|--|--------------|
| Feed f in steel < 1100 N/mm ² | 0.12 mm/rev. |
| Shank tolerance | h6 |
| Overhang L_1 | 43 mm |

| | |
|---|--|
| Nominal $\varnothing D_c$ | 4.03 mm |
| Shank $\varnothing D_s$ | 4 mm |
| Overall length L | 77 mm |
| Flute length L_c | 21 mm |
| Number of cutting edges Z | 4 |
| recommended drill \varnothing in steel < 1100 N/mm ² | 3.8 mm |
| Bore \varnothing tolerance | H7 |
| Coating | TiAlN |
| Tool material | Solid carbide |
| Standard | Manufacturer's standard |
| Through-coolant | no |
| Shank | DIN 6535 HA with h6 |
| Application for type of drilling | for through holes |
| Colour ring | green |
| Type of product | Reaming tool with non-detachable cutters |