

Garant
Solid carbide reamer HPC through hole, TiAlN, Nominal Ø DC: 15H7 mm

Order data

Order number	164348 15H7
GTIN	4045197546227
Item class	10N

Description
Version:

Version suitable for NC with straight shank Ø for standard arbors especially in **hydraulic chucks** or **high precision collet chucks**. This gives **very high concentricity** and **process reliability**. No need to procure special collets. With internal coolant supply for **HPC applications** to reduce manufacturing costs.

Reamers finish ground to match your specifications.

With short, straight flutes.

Application:

For **HPC/HSM reaming** of **through holes**.

Application for type of drilling: for through holes

Bore Ø tolerance: H7

Number of cutting edges Z: 6

Bore Ø tolerance: H7

Flute length L_c : 22 mm

Overhang L_1 : 77 mm

Overall length L: 130 mm

Number of cutting edges Z: 6

Shank Ø D_s : 16 mm

Technical description

Shank tolerance	h6
Feed f in steel < 60 HRC	0.15 mm/rev.
Nominal Ø D_c	15 mm
Overhang L_1	77 mm

Shank $\varnothing D_s$	16 mm
Overall length L	130 mm
Flute length L_c	22 mm
Number of cutting edges Z	6
recommended drill \varnothing in steel < 60 HRC	14.9 mm
Bore \varnothing tolerance	H7
Coating	TiAlN
Tool material	Solid carbide
Standard	Manufacturer's standard
Through-coolant	yes, with 25 bar
Shank	DIN 6535 HA with h6
Machining strategy	HPC
Application for type of drilling	for through holes
Colour ring	red
Type of product	Reaming tool with non-detachable cutters