

Garant
Solid carbide reamer HPC blind hole, TiAlN, Nominal Ø DC: 4H7 mm

Order data

Order number	164351 4H7
GTIN	4045197852915
Item class	10N

Description
Version:

Version suitable for NC with straight shank Ø for standard arbors especially in **hydraulic chucks** or **high precision collet chucks**. This gives **very high concentricity** and **process reliability**. No need to procure special collets. With internal coolant supply for **HPC applications** to reduce manufacturing costs.

Reamers finish ground to match your specifications.

With short, straight flutes.

Application:

For **HPC/HSC reaming** of **blind holes**.

Application for type of drilling: for blind holes

Bore Ø tolerance: H7

Number of cutting edges Z: 4

Bore Ø tolerance: H7

Flute length L_c: 12 mm

Overhang L₁: 34 mm

Overall length L: 75 mm

Number of cutting edges Z: 4

Shank Ø D_s: 6 mm

Technical description

Overhang L ₁	34 mm
Feed f in stainless steel < 900 N/mm ²	0.06 mm/rev.
Overall length L	75 mm
recommended drill Ø in INOX < 900 N/mm ²	3.9 mm

Number of cutting edges Z	4
Shank $\varnothing D_s$	6 mm
Flute length L_c	12 mm
Shank tolerance	h6
Nominal $\varnothing D_c$	4 mm
Bore \varnothing tolerance	H7
Coating	TiAlN
Tool material	Solid carbide
Standard	Manufacturer's standard
Through-coolant	yes, with 25 bar
Shank	DIN 6535 HA to h6
Machining strategy	HPC
Application for type of drilling	for blind holes
Colour ring	blue
Type of product	Reaming tool with non-detachable cutters