

**Garant**
**HSS reamer HPC through hole, TiAlN, Nominal Ø DC: 20H7 mm**

**Order data**

Order number	164358 20H7
GTIN	4045197767837
Item class	10N

**Description**
**Version:**

**Version suitable for NC** with straight shank Ø for the standardised toolholder, specially in **hydraulic chucks** or **high-accuracy chucks**.

This ensures **very high concentricity** and **process reliability**.

It is no longer necessary to procure special arbors.

With internal coolant feed for **HPC use** to reduce production costs.

With short, straight flutes.

**Reamers finish ground to match your specifications.**

**Application:**

For **HPC/HSC reaming of through holes**.

Application for type of drilling: for through holes

Bore Ø tolerance: H7

Number of cutting edges Z: 8

Bore Ø tolerance: H7

Flute length  $L_c$ : 25 mm

Overhang  $L_1$ : 95 mm

Overall length L: 150 mm

Number of cutting edges Z: 8

Shank Ø  $D_s$ : 20 mm

**Technical description**

Overhang $L_1$	95 mm
Number of cutting edges Z	8
Shank Ø $D_s$	20 mm
Overall length L	150 mm

Nominal $\varnothing D_c$	20 mm
Flute length $L_c$	25 mm
Feed $f$ in steel $< 1100 \text{ N/mm}^2$	0.23 mm/rev.
recommended drill $\varnothing$ in steel $< 1100 \text{ N/mm}^2$	19.8 mm
Bore $\varnothing$ tolerance	H7
Coating	TiAlN
Tool material	HSS
Standard	Manufacturer's standard
Through-coolant	yes, with 25 bar
Shank	DIN 6535 HA with h6
Machining strategy	HPC
Application for type of drilling	for through holes
Colour ring	green
Type of product	Reaming tool with non-detachable cutters