

Garant
HSS reamer HPC through hole, TiAlN, Nominal Ø DC: 7H7 mm

Order data

Order number	164358 7H7
GTIN	4045197767707
Item class	10N

Description
Version:

Version suitable for NC with straight shank Ø for the standardised toolholder, specially in **hydraulic chucks** or **high-accuracy chucks**.

This ensures **very high concentricity** and **process reliability**.

It is no longer necessary to procure special arbors.

With internal coolant feed for **HPC use** to reduce production costs.

With short, straight flutes.

Reamers finish ground to match your specifications.

Application:

For **HPC/HSC reaming of through holes**.

Application for type of drilling: for through holes

Bore Ø tolerance: H7

Number of cutting edges Z: 6

Bore Ø tolerance: H7

Flute length L_c : 16 mm

Overhang L_1 : 58 mm

Overall length L: 100 mm

Number of cutting edges Z: 6

Shank Ø D_s : 8 mm

Technical description

Feed f in steel < 1100 N/mm ²	0.12 mm/rev.
Number of cutting edges Z	6
Overall length L	100 mm
Overhang L_1	58 mm

Shank $\varnothing D_s$	8 mm
Flute length L_c	16 mm
Nominal $\varnothing D_c$	7 mm
recommended drill \varnothing in steel < 1100 N/mm ²	6.9 mm
Bore \varnothing tolerance	H7
Coating	TiAlN
Tool material	HSS
Standard	Manufacturer's standard
Through-coolant	yes, with 25 bar
Shank	DIN 6535 HA with h6
Machining strategy	HPC
Application for type of drilling	for through holes
Colour ring	green
Type of product	Reaming tool with non-detachable cutters