

Garant
HSS reamer HPC blind hole, TiAlN, Nominal Ø DC: 15H7 mm

Order data

Order number	164359 15H7
GTIN	4045197767974
Item class	10N

Description
Version:

Version suitable for NC with straight shank Ø for the standardised toolholder, specially in **hydraulic chucks** or **high-accuracy chucks**.

This ensures **very high concentricity** and **process reliability**.

It is no longer necessary to procure special arbors.

With internal coolant feed for **HPC use** to reduce production costs.

With short, straight flutes.

Reamers finish ground to match your specifications.

Application:

For **HPC/HSC reaming** of **blind holes**.

Application for type of drilling: for blind holes

Bore Ø tolerance: H7

Number of cutting edges Z: 6

Bore Ø tolerance: H7

Flute length L_c : 22 mm

Overhang L_1 : 58 mm

Overall length L: 130 mm

Number of cutting edges Z: 6

Shank Ø D_s : 16 mm

Technical description

Shank Ø D_s	16 mm
Feed f in steel < 1100 N/mm ²	0.18 mm/rev.
Overall length L	130 mm
Number of cutting edges Z	6

Flute length L_c	22 mm
Nominal $\varnothing D_c$	15 mm
Overhang L_1	58 mm
recommended drill \varnothing in steel < 1100 N/mm ²	14.8 mm
Bore \varnothing tolerance	H7
Coating	TiAlN
Tool material	HSS
Standard	Manufacturer's standard
Through-coolant	yes, with 25 bar
Shank	DIN 6535 HA with h6
Machining strategy	HPC
Application for type of drilling	for blind holes
Colour ring	green
Type of product	Reaming tool with non-detachable cutters