

Garant
HSS reamer HPC blind hole, TiAlN, Nominal Ø DC: 30H7 mm

Order data

Order number	164359 30H7
GTIN	4045197768049
Item class	10N

Description
Version:

Version suitable for NC with straight shank Ø for the standardised toolholder, specially in **hydraulic chucks** or **high-accuracy chucks**.

This ensures **very high concentricity** and **process reliability**.

It is no longer necessary to procure special arbors.

With internal coolant feed for **HPC use** to reduce production costs.

With short, straight flutes.

Reamers finish ground to match your specifications.

Application:

For **HPC/HSC reaming** of **blind holes**.

Application for type of drilling: for blind holes

Bore Ø tolerance: H7

Number of cutting edges Z: 8

Bore Ø tolerance: H7

Flute length L_c : 25 mm

Overhang L_1 : 139 mm

Overall length L: 200 mm

Number of cutting edges Z: 8

Shank Ø D_s : 25 mm

Technical description

Flute length L_c	25 mm
Shank Ø D_s	25 mm
Feed f in steel < 1100 N/mm ²	0.4 mm/rev.
Number of cutting edges Z	8

Overhang L ₁	139 mm
Nominal Ø D _c	30 mm
Overall length L	200 mm
recommended drill Ø in steel < 1100 N/mm ²	29.7 mm
Bore Ø tolerance	H7
Coating	TiAlN
Tool material	HSS
Standard	Manufacturer's standard
Through-coolant	yes, with 25 bar
Shank	DIN 6535 HA with h6
Machining strategy	HPC
Application for type of drilling	for blind holes
Colour ring	green
Type of product	Reaming tool with non-detachable cutters