

**Garant**
**Solid carbide reamers HPC through hole, TiAlN, Nominal  $\varnothing$  DC: 8,03 mm**

**Order data**

Order number	164362 8,03
GTIN	4045197363268
Item class	10N

**Description**
**Version:**

**Version suitable for NC** with straight shank  $\varnothing$  for standard arbors especially in **hydraulic chucks** or **high precision collet chucks**. For **highest concentricity** and **process reliability**. No need to procure special collets. With internal coolant supply for **HPC applications** to reduce manufacturing costs.

**Reamer manufacturing tolerances:**

whole number sizes and  $\varnothing$  0.5: H7 to DIN 1420

1/100 sizes  $\varnothing$  3.97 – 12.03: +0.004/0

With short flutes and left-hand helix.

**Application:**

For **HPC/HSM reaming of through holes**.

Application for type of drilling: for through holes

Bore  $\varnothing$  tolerance: 0 / 0.004

Number of cutting edges Z: 6

Bore  $\varnothing$  tolerance: 0 / 0.004

Flute length  $L_c$ : 16 mm

Overhang  $L_1$ : 60 mm

Overall length L: 100 mm

Number of cutting edges Z: 6

Shank  $\varnothing$   $D_s$ : 8 mm

**Technical description**

Shank tolerance	h6
Nominal $\varnothing$ $D_c$	8.03 mm
Overhang $L_1$	60 mm

Feed f in steel < 1100 N/mm <sup>2</sup>	0.6 mm/rev.
Shank Ø D <sub>s</sub>	8 mm
Overall length L	100 mm
Flute length L <sub>c</sub>	16 mm
Number of cutting edges Z	6
recommended drill Ø in steel < 1100 N/mm <sup>2</sup>	7.9 mm
Bore Ø tolerance	0 / 0.004
Coating	TiAlN
Tool material	Solid carbide
Standard	Manufacturer's standard
Through-coolant	yes
Shank	DIN 6535 HA with h6
Machining strategy	HPC
Application for type of drilling	for through holes
Colour ring	green
Type of product	Reaming tool with non-detachable cutters