

Garant
Solid carbide reamers HPC through hole, TiAlN, Nominal Ø DC: 9,98 mm

Order data

| | |
|--------------|---------------|
| Order number | 164362 9,98 |
| GTIN | 4045197363282 |
| Item class | 10N |

Description
Version:

Version suitable for NC with straight shank Ø for standard arbors especially in **hydraulic chucks** or **high precision collet chucks**. For **highest concentricity** and **process reliability**. No need to procure special collets. With internal coolant supply for **HPC applications** to reduce manufacturing costs.

Reamer manufacturing tolerances:

whole number sizes and Ø 0.5: H7 to DIN 1420

1/100 sizes Ø 3.97 – 12.03: +0.004/0

With short flutes and left-hand helix.

Application:

For **HPC/HSM reaming of through holes**.

Application for type of drilling: for through holes

Bore Ø tolerance: 0 / 0.004

Number of cutting edges Z: 6

Bore Ø tolerance: 0 / 0.004

Flute length L_c : 20 mm

Overhang L_1 : 76 mm

Overall length L: 120 mm

Number of cutting edges Z: 6

Shank Ø D_s : 10 mm

Technical description

| | |
|--|-------------|
| Shank tolerance | h6 |
| Feed f in steel < 1100 N/mm ² | 0.6 mm/rev. |
| Overhang L_1 | 76 mm |

| | |
|---|--|
| Nominal $\varnothing D_c$ | 9.98 mm |
| Shank $\varnothing D_s$ | 10 mm |
| Overall length L | 120 mm |
| Flute length L_c | 20 mm |
| Number of cutting edges Z | 6 |
| recommended drill \varnothing in steel < 1100 N/mm ² | 9.8 mm |
| Bore \varnothing tolerance | 0 / 0.004 |
| Coating | TiAlN |
| Tool material | Solid carbide |
| Standard | Manufacturer's standard |
| Through-coolant | yes |
| Shank | DIN 6535 HA with h6 |
| Machining strategy | HPC |
| Application for type of drilling | for through holes |
| Colour ring | green |
| Type of product | Reaming tool with non-detachable cutters |