

Garant
Solid carbide reamers HPC blind hole, TiAlN, Nominal Ø DC: 4,98 mm

Order data

| | |
|--------------|---------------|
| Order number | 164392 4,98 |
| GTIN | 4045197363466 |
| Item class | 10N |

Description
Version:

Version suitable for NC with straight shank Ø for standard arbors especially in **hydraulic chucks** or **high precision collet chucks**. For **highest concentricity** and **process reliability**. No need to procure special collets. With internal coolant supply for **HPC applications** to reduce manufacturing costs.

Reamer manufacturing tolerances:

whole number sizes and Ø 0.5: H7 to DIN 1420

1/100 sizes Ø 3.97 – 12.03: +0.004/0

With short, straight flutes.

Application:

For **HPC/HSC reaming** of **blind holes**.

Application for type of drilling: for blind holes

Bore Ø tolerance: 0 / 0.004

Number of cutting edges Z: 4

Bore Ø tolerance: 0 / 0.004

Flute length L_c : 12 mm

Overhang L_1 : 35 mm

Overall length L: 75 mm

Number of cutting edges Z: 4

Shank Ø D_s : 6 mm

Technical description

| | |
|-----------------|---------|
| Shank tolerance | h6 |
| Nominal Ø D_c | 4.98 mm |
| Overhang L_1 | 35 mm |

| | |
|---|--|
| Feed f in steel < 1100 N/mm ² | 0.4 mm/rev. |
| Shank Ø D _s | 6 mm |
| Overall length L | 75 mm |
| Flute length L _c | 12 mm |
| Number of cutting edges Z | 4 |
| recommended drill Ø in steel < 1100 N/mm ² | 4.9 mm |
| Bore Ø tolerance | 0 / 0.004 |
| Coating | TiAlN |
| Tool material | Solid carbide |
| Standard | Manufacturer's standard |
| Through-coolant | yes |
| Shank | DIN 6535 HA with h6 |
| Machining strategy | HPC |
| Application for type of drilling | for blind holes |
| Colour ring | green |
| Type of product | Reaming tool with non-detachable cutters |