

Garant
Solid carbide reamers HPC blind hole, TiAlN, Nominal Ø DC: 8,02 mm

Order data

Order number	164392 8,02
GTIN	4045197363619
Item class	10N

Description
Version:

Version suitable for NC with straight shank Ø for standard arbors especially in **hydraulic chucks** or **high precision collet chucks**. For **highest concentricity** and **process reliability**. No need to procure special collets. With internal coolant supply for **HPC applications** to reduce manufacturing costs.

Reamer manufacturing tolerances:

whole number sizes and Ø 0.5: H7 to DIN 1420

1/100 sizes Ø 3.97 – 12.03: +0.004/0

With short, straight flutes.

Application:

For **HPC/HSC reaming of blind holes**.

Application for type of drilling: for blind holes

Bore Ø tolerance: 0 / 0.004

Number of cutting edges Z: 6

Bore Ø tolerance: 0 / 0.004

Flute length L_c : 16 mm

Overhang L_1 : 60 mm

Overall length L: 100 mm

Number of cutting edges Z: 6

Shank Ø D_s : 8 mm

Technical description

Overhang L_1	60 mm
Shank tolerance	h6
Nominal Ø D_c	8.02 mm

Feed f in steel < 1100 N/mm ²	0.6 mm/rev.
Shank Ø D _s	8 mm
Overall length L	100 mm
Flute length L _c	16 mm
Number of cutting edges Z	6
recommended drill Ø in steel < 1100 N/mm ²	7.9 mm
Bore Ø tolerance	0 / 0.004
Coating	TiAlN
Tool material	Solid carbide
Standard	Manufacturer's standard
Through-coolant	yes
Shank	DIN 6535 HA with h6
Machining strategy	HPC
Application for type of drilling	for blind holes
Colour ring	green
Type of product	Reaming tool with non-detachable cutters