

**Garant**
**Solid carbide reamers HPC blind hole, TiAlN, Nominal Ø DC: 9,99 mm**

**Order data**

Order number	164392 9,99
GTIN	4045197363657
Item class	10N

**Description**
**Version:**

**Version suitable for NC** with straight shank Ø for standard arbors especially in **hydraulic chucks** or **high precision collet chucks**. For **highest concentricity** and **process reliability**. No need to procure special collets. With internal coolant supply for **HPC applications** to reduce manufacturing costs.

**Reamer manufacturing tolerances:**

whole number sizes and Ø 0.5: H7 to DIN 1420

1/100 sizes Ø 3.97 – 12.03: +0.004/0

With short, straight flutes.

**Application:**

For **HPC/HSC reaming** of **blind holes**.

Application for type of drilling: for blind holes

Bore Ø tolerance: 0 / 0.004

Number of cutting edges Z: 6

Bore Ø tolerance: 0 / 0.004

Flute length  $L_c$ : 20 mm

Overhang  $L_1$ : 76 mm

Overall length L: 120 mm

Number of cutting edges Z: 6

Shank Ø  $D_s$ : 10 mm

**Technical description**

Overhang $L_1$	76 mm
Nominal Ø $D_c$	9.99 mm
Shank tolerance	h6

Feed f in steel < 1100 N/mm <sup>2</sup>	0.6 mm/rev.
Shank Ø D <sub>s</sub>	10 mm
Overall length L	120 mm
Flute length L <sub>c</sub>	20 mm
Number of cutting edges Z	6
recommended drill Ø in steel < 1100 N/mm <sup>2</sup>	9.8 mm
Bore Ø tolerance	0 / 0.004
Coating	TiAlN
Tool material	Solid carbide
Standard	Manufacturer's standard
Through-coolant	yes
Shank	DIN 6535 HA with h6
Machining strategy	HPC
Application for type of drilling	for blind holes
Colour ring	green
Type of product	Reaming tool with non-detachable cutters