

Metal band saw blade 27×2950, TPI: 5/8



Order data

| Order number | 173680 5/8 |
|--------------|---------------|
| GTIN | 4045197254085 |
| Item class | 16F |

Description

Version:

RÖNTGEN – **bi-alpha-cobalt: High-performance bi-metal band saw blade** with high chrome content **spring steel backing** and cobalt alloyed (M42) HSS tooth tips (67–69HRC). **Extreme tooth tip hardness, flexible backing.**

Application:

Variable pitch teeth 0° – very low vibration, for a large range of cross sections (for pipes and profiles, solid materials up to maximum 70 mm).

Variable pitch teeth 10° – general purpose for a wide range of cross-sections (for solid material from 50 mm).

Regular pitch teeth 0° – for small to medium cross-sections up to maximum 70 mm engagement length.

Regular pitch teeth 10° – for large cross-sections from 50 mm engagement.

Note

Running in a new blade: See GARANT machining handbook No. 110010 and information page.

Tool material: HSS Co 8 Tooth type: combi Rake: 0 degrees Tooth type: combi Rake: 0 degrees Width: 27 mm



Thickness: 0.9 mm Length: 2950 mm

Technical description

| Length | 2950 mm |
|-----------------|----------------------|
| Width | 27 mm |
| Thickness | 0.9 mm |
| Tooth type | combi |
| Rake | 0 degrees |
| Tool material | HSS Co 8 |
| Type of product | Metal band saw blade |