


Circular saw blade fine, Ø×thickness: 225X2/K mm

Order data

Order number	177050 225X2/K
GTIN	4045197095374
Item class	12T

Description
Version:

Precise format and good quality for a competitive price. **Vaporised surface** protects against edge build-up.

Application:

For low speed machines (approx. 50 rpm).

Pitch t: (tooth form).

- **4 mm (BW) – For profiles and pipes with 1.0 – 1.5 mm wall thickness.**
- **5 / 6 mm (HZ) – For medium profiles, pipes and solid bar with 1.5 – 20 mm wall thickness / cross-section.**
- **7 / 8 mm (HZ) – For thick profiles and solid bar up to approx. 50 mm wall thickness / cross-section.**
- **10 – 16 mm (HZ) – For extra thick cross-sections and solid bar more than 50 mm.**

Note:

- **For stainless steels (such as V2A) the correct cutting speed and lubrication is crucial (see information in the machining handbook No. 110020).**
- **The concentricity and axial run-out values are considerably better than those to DIN 1840, in some cases by up to 50 %.**

Tool material: HSS

Thickness: 2 mm

Bore Ø: 32 mm

No. of teeth Z: 180
Pitch t: 4 mm
Number of drive holes: 2
Drive hole \varnothing : 8 mm

Technical description

\varnothing	225 mm
Bore \varnothing	32 mm
suitable for saw makes	Eisele
Thickness	2 mm
Pitch t	4 mm
No. of teeth Z	180
Number of drive holes	2
Drive hole \varnothing	8 mm
Drive hole pitch circle	45 mm
Tool material	HSS
Type of product	Circular saw blade