

Re-Bo
Stainless steel circular saw blade medium, Ø×thickness: 315X3 mm


Order data

Order number	177520 315X3
GTIN	4045197245373
Item class	17B

Description

Version:

Precision toothing and very fine ground side faces. **Rake angle especially for stainless steels.**

Nitrided surface: hard, durable protection against edge build-up.

Application:

Pitch t: (tooth form)

- **3 mm (BW)** – For thin pipes, profiles, sheet metal with 1 – 2 mm wall thickness.
- **4 mm (BW)** – For pipes, profiles, sheet metal with 1.5 – 4 mm wall thickness.
- **6 mm (HZ)** – For pipes, profiles and solid material above 4 mm wall thickness or cross-section up to a maximum of. 50 mm.
- **8 mm (HZ)** – For solid material above 50 mm.

Suitable for :

EISELE and **TRENNJAEGER** cold circular saws.

Note:

- **For optimum performance and service life: use coolant concentrate No. 084260.**
- **The concentricity and axial run-out values are considerably better than the figures according to DIN 1840, in some cases by up to 50 %.**

Tool material: HSS E

Thickness: 3 mm

Bore Ø: 40 mm

No. of teeth Z: 160

Pitch t: 6 mm
Number of drive holes: 2; 4
Drive hole Ø: 9; 12 mm

Technical description

Pitch t	6 mm
Thickness	3 mm
Bore Ø	40 mm
Ø	315 mm
No. of teeth Z	160
Drive hole pitch circle	55; 64 mm
Number of drive holes	2; 4
Drive hole Ø	9; 12 mm
Tool material	HSS E
Type of product	Circular saw blade